

GEPON OLT

Optical Module

**OLT-GSFP-20+****OLT-GSFP-20++**

Product Features

- Compatible IEEE 802.3ah 1000BASE-PX20+/PX20++ GEPON application
- Applied to EPON OLT for a Single Fiber Bi-directional EPON System
- SFP, Single SC connector, Digital Diagnostic Interface Compliant with SFF-8472
- Burst Digital Receiving Signal Strength Indication (RSSI)
- Single 3.3V power supply
- Operation case temperature -10~70°C for commercial
- RoHS-6 compliance

Absolute Maximum Ratings

Parameter	Unit	Min.	Typical	Max.
Power Supply	V	0		4.2
Storage Ambient Temperature	°C	-40		85
Operating Case Temperature	°C	-10		70
Operating Relative Humidity	%	5		95
Receiver Damaged Threshold	dBm	0		


Operating Condition

Parameter	Unit	Min.	Typical	Max.
Power Supply	V	3.1	3.3	3.5
Operating Case Temp for C-temp	°C	-10		70
Operating Relative Humidity	%	5		95
Data Rate(TX/RX)	Gbit/s		1.25	

Characteristics

Parameter	Unit	Min.	Typical	Max.
GSFP-OLT-20+				
TX Central Wavelength	nm	1480	1490	1500
Spectral Width (-20dB)	nm			1
SMSR	dB	30		
Mean Launched Power	dBm	2		7
Mean Launched Power (TX Off)	dBm			-39
Extinction Ratio(Note 1)	dB	9		
TX Total Jitter	UI			0.43
Rise/Fall Time (20%-80%)	ps			260
RIN _{is} OMA	dB/Hz			-115
Optical Return Loss Tolerance	dB			-12
Transmitteranddispersion Penalty(20km G.652)	dB			2.3
TX Optical Eye Mask	Compliant With IEEE Std 802.3ah™-2004			
Receive Wavelength	nm	1260	1310	1360
Sensitivity (Note 2)	dBm			-30
Overload	dBm	-6		
Receiver Threshold Settling Time	ns			250
RX Dynamic Range(Note 3)	dBm	-30		-6
LOS-Deassert	dBm			-31
LOS-Assert	dBm	-45		
SD Hysteresis	dB	0.5		6
Receiver Reflectance	dB			-12
Electrical Interface Characteristics				
Power Supply Current	mA			300
Data Input Differential Swing	mV	200		1600
Data Differential Impedance	Ω	90	100	110
TTL Input -Low	V	0		0.8
TTL Input -High	V	2.0		Vcc
TTL Output -Low	V	0		0.4
TTL Output -High	V	2.4		Vcc
Data Output Differential Swing	mV	400		1600
Los Assert Time	ns			500
Los Deassert Time	ns			500


Note1: Measured with PRBS 2⁷-1 test pattern @1.25Gbps, Low Pass Filter is on.
Note2: Measured with a PRBS 2⁷-1 test pattern @1.25Gbps and ER=10dB, BER =10⁻¹² ,
Note3: RX Dynamic Range Definition



Characteristics

Parameter	Unit	Min.	Typical	Max.
GSFP-OLT-20++				
TX Central Wavelength	nm	1480	1490	1500
Spectral Width (-20dB)	nm			1
SMSR	dB	30		
Mean Launched Power	dBm	5		8
Mean Launched Power (TX Off)	dBm			-39
Extinction Ratio(Note 1)	dB	9		
TX Total Jitter	UI			0.43
Rise/Fall Time (20%-80%)	ps			260
RIN _{is} OMA	dB/Hz			-115
Optical Return Loss Tolerance	dB			-12
Transmitter and dispersion Penalty(20km G.652)	dB			2.3
TX Optical Eye Mask	Compliant With IEEE Std 802.3ah™-2004			
Receive Wavelength	nm	1260	1310	1360
Sensitivity (Note 2)	dBm			-33
Overload	dBm	-6		
Dynamic Rang	dB	25		
Receiver Threshold Settling Time	ns			250
RX Dynamic Range(Note 3)	dBm	-30		-6
LOS-Deassert	dBm			-34
LOS-Assert	dBm	-45		
SD Hysteresis	dB	0.5		6
Receiver Reflectance	dB			-12
Electrical Interface Characteristics				
Power Supply Current	mA			300
Data Input Differential Swing	mV	200		1600
Data Differential Impedance	Ω	90	100	110
TTL Input -Low	V	0		0.8
TTL Input -High	V	2.0		Vcc
TTL Output -Low	V	0		0.4
TTL Output -High	V	2.4		Vcc
Data Output Differential Swing	mV	400		1600
Los Assert Time	ns			500
Los Deassert Time	ns			500

Note1: Measured with PRBS 2⁷-1 test pattern @1.25Gbps, Low Pass Filter is on.
Note2: Measured with a PRBS 2⁷-1 test pattern @1.25Gbps and ER=10dB, BER <10⁻¹² ,
Note3: RX Dynamic Range Definition



Ordering Information

Model	Description
OLT-GSFP-20+	OLT SFP module, PX 20+ standard, downlink 1.25G/uplink 1.25G, TX wavelength 1490nm, RX wavelength 1310nm, SC interface
OLT-GSFP-20++	OLT SFP module, PX 20++ standard, downlink 1.25G/uplink 1.25G, TX wavelength 1490nm, RX wavelength 1310nm, SC interface

Copyright © Shanghai Baud Data Communication Co., Ltd. 2019. All Rights Reserved.

This document is BDCOM Public Information. BDCOM reserves the right to alter, update and otherwise change the information contained in the document from time to time.
www.bdc.com.cn

