

P1704 Series

EPON Multi-service
Broadband Access Home
Gateway Unit(HGU)

Product Overview

BDCOM P1704 Series is a smart HGU with integrated wireless, VoIP and CATV function.

It is oriented for the integrated multi-service network in telecom operator network.

BDCOM P1704 Series is complied with the international standard IEEE802.3ah and PRC Communication Industry Standard (YD/T 1475-2006) and China Telecom EPON Technical Requirement CTC.

P1704 series includes 4 models: P1704-4F-E, P1704-4GV, P1704-4GV-22A, P1704-4GVC-S.



Product Characteristics

Excellent Access Capacity

It supports the PON transmission rate of downlink 1.25Gbps/ uplink 1.25Gbps. Connected with BDCOM OLT, it can realize 1:64 splitting ratio. The covering radius of the network can reach to 20km.

Secure Service Carrying Ability

For ensuring the secure service carrying ability of ONU, BDCOM has developed techniques including VLAN, STP, port isolation, ACL, QoS and Broadcast Storm Control.

High Service Control Capability

It supports DBA and Rate-Limit. It supports advanced dynamic bandwidth distribution and accurate bandwidth limit, which enables users to share 1.25Gbps bandwidth resource appropriately. It also supports QOS function, which guarantees a reliable service quality and service priority.

Rich OAM Function

It supports the standard OAM defined by China Telecom CTC2.1/3.0, including configuration, alarm, performance monitoring, fault isolation and security management, and it also supports private OAM defined by BDCOM.

Complete Interaction Capacity

It is complied with IEEE802.3ah and relevant requirements for PRC Community Industry Standard (YD/T 1475-2006) and China Telecom CTC2.1/3.0.

Advanced Energy-saving Technique

It supports the "GreenTouch" architecture and "Smart@CHIP".



Support 1.25Gbps uplink/downlink bandwidth



Efficient bandwidth usage and Ethernet services



The splitting ratio ups to 1:64

Model Lists

P1704-4F-E

GPON Multi-service Broadband Access Home Gateway Unit(HGU)



- 1 SC/UPC
- 1 GE + 3 FE TX
- 300Mbps Wireless

P1704-4GV

GPON Multi-service Broadband Access Home Gateway Unit(HGU)



- 1 SC/UPC
- 4 GE TX
- 300Mbps wireless
- 2 POTS

P1704-4GV-22A

GPON Multi-service Broadband Access Home Gateway Unit(HGU)



- 1 SC/UPC
- 4 GE TX
- 1200Mbps wireless
- 2 POTS


P1704-4GVC-S

GPON Multi-service Broadband Access Home Gateway Unit(HGU)



- 1 SC/APC
- 4 GE TX
- 1 RF port
- 300Mbps wireless
- 2 POTS

Application Diagram



System Performance

| Item | | P1704-4F-E | P1704-4GV | P1704-4GV-22A | P1704-4GVC-S |
|------------------------------|-----------------------|--------------------------------------|--|--|--|
| Service interface | | | | | |
| PON ports | | 1 SC/UPC | 1 SC/UPC | 1 SC/UPC | 1 SC/APC |
| UNI ports | | 1 GE + 3 FE TX | 4 GE TX | 4 GE TX | 4 GE TX + 1 RF |
| WIFI | | 300M | 300M | 1200M | 300M |
| Voice | | / | 2 | 2 | 2 |
| USB | | / | 1 | 1 | 1 |
| Optical power | TX power | 0.5~5dBm | 0.5~5dBm | 0.5~5dBm | 0.5~5dBm |
| | RX sensitive | <-28dBm | <-28dBm | <-28dBm | <-28dBm |
| System capacity | | | | | |
| DRAM (MB) | | 128 | 128 | 128 | 128 |
| Flash (MB) | | 128 | 128 | 128 | 128 |
| MAC table | | 2K | 2K | 2K | 2K |
| VLAN ID | | 4K | 4K | 4K | 4K |
| Power supply | | | | | |
| AC adaptor | | Input: 100-240V AC Output: 12V/1A | Input: 100-240V AC Output: 12V/1.5A | Input: 100-240V AC Output: 12V/1.5A | Input: 100-240V AC Output: 12V/1.5A |
| Max. consumption (W) | | 8 | 15 | 15 | 15 |
| Appearance | | | | | |
| Chassis | Dimensions (WxDxH mm) | 140 x 105 x 30 | 230 x 140 x 34.9 | 230 x 140 x 34.9 | 230 x 140 x 34.9 |
| | Weight(Kg)(empty) | 0.2 | 0.4 | 0.4 | 0.5 |
| Package | Dimensions (WxDxH mm) | 277 x 176 x 38 | 325 x 255 x 48 | 325 x 255 x 48 | 325 x 255 x 48 |
| | Weight (Kg) | 0.4 | 0.6 | 0.7 | 0.7 |
| Environmental Specifications | | | | | |
| Operating | Temperature | -0℃ -45℃ | -0℃ -45℃ | -0℃ -45℃ | -0℃ -45℃ |
| | Humidity | 10%~85% (non-condensing) | 10%~85% (non-condensing) | 10%~85% (non-condensing) | 10%~85% (non-condensing) |
| Storage | Temperature | -40℃ -85℃ | -40℃ -85℃ | -40℃ -85℃ | -40℃ -85℃ |
| | Humidity | 5%-95% (non-condensing) | 5%-95% (non-condensing) | 5%-95% (non-condensing) | 5%-95% (non-condensing) |
| System capacity | | | | | |
| Accessories | | | Power adaptor | | |

Ordering Information

| Model | Description |
|---------------|---|
| P1704-4F-E | FTTH/O ONU, 1 EPON port (SC/UPC), 1 GE + 3 FE TX ports, external dual antenna(300M WiFi), plastic hull, DC12V/1A, external adaptor |
| P1704-4GV | FTTH/O ONU, 1 EPON port (SC/UPC), 4 GE TX ports, 2 POTS, external dual antenna(300M WiFi), plastic hull, DC12V/1.5A, external adaptor |
| P1704-4GV-22A | FTTH/O ONU, 1 EPON port (SC/UPC), 4 GE TX ports, 2 POTS, external quadruple antenna(1200M WiFi), plastic hull, DC12V/1.5A, external adaptor |
| P1704-4GVC-S | FTTH/O ONU, 1 EPON port (SC/APC), 4 GE TX ports, 2 POTS, 1 RF(British system), external dual antenna(300M WiFi), plastic hull, DC12V/1.5A, external adaptor |

Technical Specifications

Standards

- IEEE 802.3ah
- PRC Community Industry Standard (YD/T 1475-2006);
- IEEE 802.1D, Spanning Tree
- IEEE 802.1Q, VLAN
- IEEE 802.1w, RSTP
- ITU-T Y.1291

VLAN

- 4K VLAN
- Port based VLAN
- IEEE 802.1Q VLAN
- Tag/Transparent/Aggregation
- /Trunk/Translation mode VLAN
- CTC2.1/3.0 defined VLAN

IP Service

- DHCP server/client
- Routing/Bridging/Hybrid mode
- DNS, DDNS
- PPPoE
- NAT/NAPT

QoS

- Backpressure flow control (half-duplex)
- IEEE 802.3x flow control (full duplex)
- Against Head of Line mechanism
- IEEE 802.1p, CoS
- Four priority queues on each port
- WR, SP and FIFO queue schedule algorithms
- Port rate limit
- SLA and DBA

Management

- Management modes including CLI, HTTP, SNMP, TR069 and TELNET
- Software upgrade through TFTP and WEB, OMCI, etc.
- Local or server syslog

EPON Service

- AES128 algorithm encryption
- MAC/Loid/Hybrid authentication

Voice Service

- SIP, H.248, T.38 FAX
- Three-way calling
- Call waiting
- Hot-line calling

Network Security

- MAC address number limit
- MAC filter
- Port protect

Multicast

- IGMP-Snooping
- CTC defined dynamic multicast function
- MLD-Snooping
- Multicast group limitation
- Multicast fast-leave

Reliability

- Loop detection
- Dying-Gasp
- TX/RX optical power alarm

Wireless

- 802.11b/g/n
- 802.11 ac(P1704-4GV-22A)
- 2x2 MIMO
- Multi SSID
- SSID encryption
- Configurable Channel