


Product Description

The MW12 is a whole home Mesh WiFi system designed for medium to large households with a high speed broadband service. Powered by Tenda Mesh technology, it creates a distributed network with several nodes throughout your home. It carries a 900 MHz strong CPU and 256 MB large memories, and is able to handle more devices on your network. All terminals can enjoy high-speed tri-band WiFi at the same time, indicating low latency for internet games, smooth streaming of 4K videos and VR HD applications. It features easy and wire-free installation and allows both auto-networking and manual addition. With seamless roaming around the house, the MW12 creates a high-speed and intelligent Mesh WiFi system throughout your home.




Tri-band AC2100 Mesh solution exploits the full potential of your Fiber access. Three bands(2.4GHz, 5GHz-1, 5GHz-2) are used as backhaul to eliminate the lag while multiple devices streaming at the same time.



It adopts 5GHz dedicated powerful WLAN full-featured front -end module, equipped with integrated signal amplifier. The concentrated signal makes sure stronger and more stable Multi -story home WiFi coverage. You can enjoy best signal in any conner.



MW12 units work together under one unified network supported by 802.11k/v/r protocal, always connect your devices with the best performance node while the devices freely moving around in your house.



Any Nova-series product (MW3, MW5, MW5S, MW5G, MW6, MW12) can be used as an extra unit in existing Nova network easily to meet varies house type requirement.



Equipped with dual-core 900MHz CPU, 256M DDR3 memory supporting MU-MIMO technology to bring lag-free experience for over 100 devices.



Quality of Service (QoS) optimizes traffic so that stream with higher priority can pass first, which brings better performance for 4K video, HD-VR Game and etc.



All Nova units are delivered pre-paired right out of the box, and a new node can be added to original Nova network with 3 simple steps.

Easily manage your Nova units with Tenda WiFi APP. The real -time progress of online devices is all in your hands.



With its stylish design, you can display Nova like a piece of workart in your entertainment center.

Hardware Specifications			
Processor	Dual core 900MHz CPU		
RAM	256MB DDR3		
RF	2.4G: 18.5±1dBm@MCS7 VHT40 5.1G: 18.5±1dBm@MCS9 VHT80 5.4G-5.8G: 21±1dBm@MCS9 VHT80(dedicated backhaul)		
Standard&Protocol	IEEE802.11a/b/g/n/ac IEEE 802.3, IEEE 802.3u, IEEE 802.3ab		
Ethernet Interface	3 x 10/100/1000Mbps RJ45 ports per node		
Antennas	4 x Internal antenna		
Button	1 x Reset Button		
LED Indicator	1 x Tri-color LED Indicator(Green, Yellow, Red)		
Power	Input: 100-240V—50/60Hz, 0.6A; Output: 12V1.5A		
Dimensions	100 x 100 x 100mm (3.1 x 3.1 x 3.1in)		
Wireless Features			
Wireless Standards	IEEE802.11a/b/g/n/ac (WiFi 5 wave 2)		
Wireless roaming	Comply with IEEE802.11k/v/r		
Mesh network Standard	IEEE802.11s		
Rate	2.4GHz: 300Mbps 5GHz-1: 867Mbps 5GHz-2: 867Mbps		
Frequency	2.4~2.4835GHz 5.15~5.25GHz 5.47~5.725GHz (for EU countries) 5.725~5.85GHz		
Basic Features	SSID Broadcast Beam Forming MU-MIMO AP Steering Band Steering		
Wireless Security	WPA-PSK/WPA2-PSK(default)		

Software Features		
Operating Mode	Router Mode,Bridge Mode	
Internet Connection Type	PPPoE, Dynamic IP, Static IP, PPPoE(Russia), PPTP(Russia), L2TP(Russia)	
DHCP Server	DHCP Server, DHCP Client List	
Virtual Server	Port Forwarding, DMZ Host, UPnP	
Parental Control	Client Filter Manually setting up DNS server	
Firewall	Forbid TCP/UDP flood attack VPN(PPTP/L2TP/IPsec)pass through	
Special Features	Dedicated Backhaul Turbo Backhaul Mode Fast Roaming Smart QoS (Gaming, Video & Audio, Download)	
Others	Auto-sensing internet connection Support App management and Remote management Guest Network Firmware upgrade online	
Others		
Operating Temperature	Storage Temperature: -40 °C - 70 °C	
Storage Temperature	-40 ~ 70 ⊠	
Operating Humidity	10%~90% RH non-condensing	
Storage Humidity	5%~90% RH non-condensing	
APP installation	Available in iOS 8.0 or later, Android 4.0 or later	
Certification	CE, FCC, RoHS	

SHENZHEN TENDA TECHNOLOGY CO.,LTD.

Tenda Technology Bldg.Int' I E-City, #1001 Zhong Shan Yuan Rd.,Nanshan District,Shenzhen China.

E-mail:support@tenda.com.cn Tel:+86-755-2765 7098 Fax:+86-755-2765 7178